

SS PIPE REPAIR CLAMP - HALF CIRCLE

Pipe repair clamps offer a versatile option for repairing pin-hole leaks in smaller pipes. Available in two lengths of 75mm & 150mm, the repair clamps work by providing a seal to the pipe disallowing the leak to continue providing a permanent repair solution for most common pipe sizes.

- **Locking Washer Plate:** Locks into position for easy tightening of nuts.
- **Lugs:** MIG-welded to receiver bar and fully passivated after welding. The leading edge is rounded to prevent them from catching bolt bars during installation.
- **Shell:** 2B finish. Grade of stainless steel, Type 316.
- Fully passivated after welding to restore the original passive state of the 316 stainless steel.
- **Bolts:** Thread-rolled for strength and coated to prevent galling. Bolts are MIG-welded to the receiver bar and fully passivated after welding.
- **Nuts/Washers:** Type 316 stainless steel. Receiver Bars: TIG-welded to shell to form a strong fusion and fully passivated after welding.
- **Gasket:** Nitrile rubber is specially formulated for water service incorporating antioxidant agents to increase shelf life. All gaskets have a grid design, tapered ends and vulcanised armour plates for easy installation and optimum sealing efficiency. Natural rubber is available on request.
- **Armour:** Heavy gauge 316 stainless steel vulcanised into the gasket at the time of moulding

NOMINAL PIPE SIZE	OUTSIDE DIAMETER
15mm	21.3mm
20mm	26.7mm
25mm	33.4mm
32mm	42.2mm
40mm	48.3mm
50mm	60.3mm
65mm	73.0mm
75mm	88.9mm
100mm	114.3mm

